



## Product Data

# Castrol Classic GP 50

Oil for Classic Vehicles

## Description

A mineral based oil of high viscosity with some anti-oxidant and load carrying treatment.

## Application

Castrol Classic GP 50 is suitable for applications requiring an oil of high viscosity and relatively low performance level such as older (vintage) engines and some motorcycles where an API SB performance level is required.

## Typical Characteristics

Name	Method	Units	Castrol Classic GP 50
Density @ 15C, Relative	ASTM D4052	g/ml	0.895
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	19.1
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	224
Viscosity Index	ASTM D2270	None	96
Pour Point	ASTM D97	°C	-18
Flash Point, PMCC	ASTM D93	°C	230
SAE Viscosity Rating	J300		50

## Product Performance Claims

API SB

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Classic GP 50

22 Jan 2016

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

Orders/Enquiries: 0345 6008125 Technical Enquiries: 0345 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353

[www.castrol.com/uk](http://www.castrol.com/uk)